



PIN OUT

P1	P2	P1	P2
1 <b>Red coax conductor</b>	1	13	13
2 <b>Green coax conductor</b>	2	14	14
3 <b>Blue coax conductor</b>	3	15	15
4 <b>Red coax drain</b>	6	4	4
5 <b>Green coax drain</b>	7	5	5
6 <b>Blue coax drain</b>	8	10	10
7	9	11	11
8	8	10	10
9	9	11	11
10	12	shell1	shell1
11	12	shell1	shell1
12			

REQUIREMENTS:

1:100% short,open and miss wire test.

2:Insulation resistance:DC300V 10MΩ(Min)

Conduction resistance 5Ω(Max)

⑦	OUTER MOLDED	BLACK 45P PVC	0.024	KG
⑥	INNER MOLDED	LEPD	0.024	KG
⑤	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	4	PCS
④	NUJI	#4-40UNC 5.2*6.1MM	2	PCS
③	CONNECTOR	HDB 15PIN/MALE BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
②	CONNECTOR	HDB 15PIN/FEMALE BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
①	CABLE	(1C*28#+D+AL+PVC)*3C+6C*28#+AL+D+B JACKET:BLACK PVC OD:8.0±0.15 MARKING:AWM STYLE 2919 80°C 30V LOW VOLTAGE COMPUTER CABLE ROHS COMPLIANT	10000	MM
NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT

LItemref	Quantity	Title/Name,designation,material,dimension etc		Article No./Reference
Designed by	ACHY	Checked by	HELEN	Approved by - date
ACHY		JUN 03,2014		JUN 03,2014
ANGLE:		File name	VGA 3+6 M-F 28AWG 10M	
UNIT:MM			32 2100	Edition
				Sheet
				1/1