



P/N:

P/N	L(MM)	T(MM)
GZS-0.5MM	500	±30
GZS-1MM	1000	±50
GZS-2MM	2000	±70
GZS-3MM	3000	±70
GZS-5MM	5000	±70
GZS-10MM	10000	±150
GZS-15MM	15000	±200
GZS-20MM	20000	±250
GZS-30MM	30000	±350

PIN OUT

P1		P2	P1	P2
1	<b>Red coax conductor</b>	1	9	9
2	<b>Green coax conductor</b>	2	11	11
3	<b>Blue coax conductor</b>	3	12	12
6	<b>Red coax drain</b>	6	13	13
7	<b>Green coax drain</b>	7	14	14
8	<b>Blue coax drain</b>	8	15	15
4		4	10	10
5		5	shell	shell

REQUIREMENTS:

1:100% short,open and miss wire test.

2:Insulation resistance:DC300V 10MΩ(Min)  
Conduction resistance 5Ω(Max)

NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT
⑥	OUTER MOLDED	BLACK 45P PVC	0.038	KG
⑤	INTER MOLDED	LDPE	0.021	KG
④	SCREW	#4-40UNC-2A,WITH BLACK PVC	4	PCS
③	FERRITE CORE	F5B:RH14.2*28.5*9.5	2	PCS
②	CONNECTOR	HDB 15PIN MALE,BLACK INSULATOR,GOLD PLATED SHELL, GOLD PLATED PIN.	2	PCS
①	CABLE	[28#(7/0.127TC)*1COAX+S(40/0.10TC)]*3C+24#(11/0.16TC)*8C+A+D(7/0.12BC)+B(16/8/0.12ALM),JACKET:BLACK HALF MATT,OD:8.5MM	L	MM

Ltemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference		
Designed by ACHY	Checked by HELEN	Approved by - date SEP 11.2013	File name VGA 3+8M/M xxM	Date SEP 11.2013	Scale FREE
ANGLE:			VGA 3+8 M TO M WITH FERRITES		
UNIT:MM			GZS-xxMM	Edition 1	Sheet 1/1